



(4) 3/8-16 UNC-2B X .56 DEEP ON A ø5.875 B.C.

DASH NO.	"C"	"AD"	CAP. DASH	"X0"
600	11.81	1.93	A	1.06
650	12.31	2.43	B	1.51
700	12.81	2.93	C	1.73
750	13.31	3.43		

GASKETS THRUUGHOUT  
 MAXIMUM FACE RUNOUT TO BE .004 T.I.R.  
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.  
 PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.



**ELECTRIC MOTORS  
 GEARMOTORS  
 AND DRIVES**

DRAWN	RDW 10/29/04
CHK	
APPD	SW 10/29/04
SCALE	3=8
REF	032530
FMF	
PREV	

TITLE **OUTLINE - 56 FRAME  
 TEFC - RIGID**

MAT'L. **GENERAL PURPOSE**

NO.	REVISION	BY & DATE	CHK	TOLERANCES UNLESS SPECIFIED		FINISH
				DEC.	INCHES	
				.X	±.1	
				.XX	±.03	
				.XXX	±.005	
				.XXXX	±.0005	
				ANG	±1/2°	